

Technical data

TransSteel 3000 C Pulse		
Mains voltage -20 / +15%	3 x 380 / 400 V. 3 x 460 V	
Mains fuse protection (slow-blow)	35 A	
Mains tolerance	-10/+15%	
Maximum primary power	11.8 kVA	
Welding current range		
MIG/MAG	10 – 300 A	
MMA	10 – 300 A	
TIG	10 – 300 A	
Welding current		
MIG/MAG		
10min/40°C (104°F) 30% ED	300 A (40%)	
10min/40°C (104°F) 100% ED	240 A	
MMA		
10min/40°C (104°F) 35% ED	300 A (40%)	
10min/40°C (104°F) 100% ED	240 A	
TIG		
10min/40°C (104°F) 35% ED	300 A (40%)	
10min/40°C (104°F) 100% ED	240 A	
Open circuit voltage	59 V	
Output voltage range		
MIG/MAG	14.5 – 38.5 V	
MMA	20.4 – 32.0 V	
TIG	10.4 – 22.0 V	
Degree of protection	IP 23	
Dimensions l x b x h	747 x 300 x 497 mm / 29.4 x 11.8 x 19.6 in	
Weight	36 kg (79.4 lb)	

Functions	TransSteel 3000C Pulse
Multiprocess	✓
Pulse	✓
SynchroPulse	✓
Wirespool size	D 200 / D 300
Wire speed	4R
Polarity reverser	✓
Cooling	Gas-cooled / water-cooled (optional)
Easy Jobs	5
Data documentation	✓
Mains operation	3-phase
Multivoltage	

Text and illustrations were accurate at the time of printing. Fronius reserves the right to make changes.
All information published in this document, despite exercising the greatest of care in its preparation, is subject to change. No legal liability is accepted. Copyright © 2022 FroniusTM. All rights reserved.